

标准型阀控密封式

FC 系列 12V

FC 系列标准型阀控密封式铅酸蓄电池具有：维护简单、安全性能卓越、自放电极小、寿命长、内阻小等优点，可任意方向使用，运输方便。

产品特性

- 通讯：汽车电话、基站等
- 安防：应急照明系统、信号系统
- 动力：电动工具、搬运机器人
- 能源：EPS 和 UPS 系统

电池规格表



电池型号	额定电压 (V)	容量 (Ah)	外形尺寸 (mm)				重量 (kg±3%)	端子	端子位置	配套螺丝
			长	宽	高	总高				
FC12-4	12	4/20HR	90	70	101	107	1.35	F1/F2	A	/
FC12-4.5	12	4.5/20HR	90	70	101	107	1.48	F1/F2	A	/
FC12-5	1	5/20HR	90	70	101	107	1.58	F1/F2	A	/
FC12-6.2	12	6.2/20HR	151	65	94	100	1.9	F1/F2	D	/
FC12-7.0	12	7.0/20HR	151	65	94	100	2.03	F1/F2	D	/
FC12-7.2	12	7.2/20HR	151	65	94	100	2.13	F1/F2	D	/
FC12-7.5	12	7.5/20HR	151	65	94	100	2.2	F1/F2	D	/
FC12-9	12	8.5/20HR	151	65	94	100	2.4	F1/F2	D	/
FC12-10	12	8.5/20HR	151	65	94	100	2.4	F1/F2	D	/
FC12-12	12	12/20HR	152	99	96	102	3.38	F1/F2	D	/
FC12-14.5	12	15/20HR	152	99	9	102	3.8	F1/F2	D	/
FC12-18P	12	18/20HR	181	77	167	167	5.15	I1	B	M5x16
FC12-18T	12	18/20HR	181	77	167	167	5.18	T1	B	M5x16
FC12-20P	12	20/20HR	181	77	167	167	6	L1	B	M5x16
FC12-20T	12	20/20HR	181	77	167	167	6	L1	B	M5x16
FC12-24AQ	12	24/10HR	165	126	174	179	7.7	L6	B	M6x20
FC12-24AT	12	24/10HR	165	126	174	174	7.7	T3	B	M6x12
FC12-26AT	12	26/10HR	166	175	126	126	83	T2	B	M6x16
FC12-26AP	12	26/10HR	166	175	126	126	8.3	L2	b	M5x16
FC12-33AP	12	33/10HR	196	130	155	179	10	L7	A	M6x20
FC12-33AT	12	33/10HR	196	130	155	167	10	T3	A	M6x16
FC12-38AQ	12	38/20HR	197	166	174	179	12.3	L6	B	M6x20
FC12-38AT	12	38/20HR	197	166	174	174	12.3	T3	B	M6x16
FC12-38BQ	12	38/20HR	198	166	174	174	12.3	L7	B	M6x20
FC12-38BT	12	38/20HR	198	166	172	172	12.3	T3	B	M6x16
FC12-42AQ	12	42/10HR	198	166	174	174	12.9	L7	B	M6x20
FC12-42AT	12	42/10HR	198	166	174	174	129	T3	B	M6x16
FC12-42QP	12	42/10HR	198	166	172	172	12.9	L3	B	M5x16
FC12-50AQ	12	50/10HR	258	134	200	200	15.5	L8	A	M6x20
FC12-50BT	12	50/10HR	229	138	208	212	15.5	T3	A	M6x16
FC12-55AP	12	55/20HR	229	138	208	226	16.2	L3	A	M8x20
FC12-55AT	12	55/10HR	229	138	208	212	17.2	T3	A	M6x16
FC12-56AQ	12	56/20HR	350	167	178	178	17.2	L9	A	M6x20
FC12-56AT	12	56/20HR	350	167	178	178	17.2	T2	A	M6x16
FC12-65AQ	12	65/10HR	350	167	178	178	20.2	L9	B	M6x20
FC12-65AT	12	65/10HR	350	167	178	178	20.2	T	B	M6x16
FC12-65BP	12	65/10HR	350	167	178	178	20.2	L4	A	M8x20
FC12-70AQ	12	70/10HR	350	167	178	178	21.3	L9	B	M6x20
FC12-70AT	12	70/10HR	350	167	178	178	21.3	T3	B	M6x16
FC12-70BT	12	70/10HR	260	169	211	215	21.7	T3	A	M6x16
FC12-70BQ	12	70/10HR	260	169	211	231	21.7	L11	A	M8x25
FC12-75AT	12	75/10HR	260	169	211	215	22	T3	A	M6x16

电池型号	额定电压 (V)	容量 (Ah)	外形尺寸 (mm)				重量 (kg±3%)	端子	端子位置	配套螺丝
			长	宽	高	总高				
FC12-75AQ	12	75/10HR	260	169	211	231	22	L11	A	M8x25
FC12-80AQ	12	80/10HR	331	174	214	240	24.8	L12	B	M8x30
FC12-80AT	12	80/10HR	331	174	214	219	24.8	T4	B	M8x16
FC12-80BT	12	80/10HR	260	169	211	215	23.3	T3	A	M6x16
FC12-80BQ	12	80/10HR	260	169	211	231	23.3	L11	A	M8x25
FC12-80BP	12	80/10HR	260	169	211	231	23.3	L4	A	M8x20
FC12-90AQ	12	90/10HR	307	169	211	227	26	L13	A	M8x30
FC12-90AT	12	90/10HR	307	169	211	215	26.5	T3	A	M6x16
FC12-90BQ	12	90/10HR	331	174	214	240	27.8	L12	B	M8x30
FC12-90BT	12	90/10HR	331	174	214	219	27.8	T4	B	M8x16
FC12-95AQ	2	95/10HR	407	174	210	233	29.5	L14	A	M8x30
FC12-95QT	12	95/10HR	407	174	210	233	29.5	T5	A	M8x16
FC12-100AQ	12	100/10HR	331	174	214	240	29	L12	B	M8x30
FC12-100AT	12	100/10HR	331	174	214	219	29	T4	B	M8x16
FC12-100BT	12	100/10HR	328	172	217	222	29	T4	A	M8x16
FC12-100DQ	12	100/10HR	407	174	210	233	33	L14	A	M8x30
FC12-100DT	12	100/10HR	407	174	210	233	33	T5	A	M8x16
FC12-100EP	12	100/10HR	328	172	222	222	29.5	L5	A	M8x20
FC12-100FT	12	100/10HR	331	174	214	219	29	T4	B	M8x16
FC12-100LQ	12	100/10HR	331	174	214	240	30.5	L12	B	M8x30
FC12-100LT	12	100/10HR	331	174	214	219	30.5	T4	B	M8x16
FC12-120AQ	12	120/20HR	331	174	214	240	23.3	L12	B	M8x30
FC12-120AT	12	120/20HR	331	174	214	219	32.3	T4	B	M8x16
FC12-120BQ	12	120/10HR	407	174	210	233	34.2	L14	A	M8x30
FC12-120BT	12	120/10HR	407	174	210	233	34.2	T5	A	M8x16
FC12-120CQ	12	120/10HR	484	171	241	241	38	L16	A	M8x30
FC12-120CT	12	120/10HR	484	171	241	241	38	T4	A	M8x16
FC12-145AQ	12	145/20HR	532	206	212	236	41.4	L17	C	M8x30
FC12-145AT	12	145/20HR	532	206	212	217	41.4	T4	C	M8x16
FC12-150AQ	12	150/10HR	484	171	241	241	43.5	L16	A	M8x30
FC12-150AT	12	150/10HR	484	171	241	241	43.5	T4	A	M8x16
FC12-150SQ	12	150/20HR	484	171	241	24	41	L16	A	M8x30
FC12-150ST	12	150/20HR	484	171	241	241	41	T4	A	M8x16
FC12-160AQ	12	160/10HR	532	206	216	240	48.3	L17	C	M8x30
FC12-160AT	12	160/10HR	532	206	216	222	48.3	T4	C	M8x16
FC12-180AQ	12	180/10HR	500	208	212	239	55.8	L17	C	M8x30
FC12-180BT	12	180/10HR	532	206	216	222	52.2	T4	C	M8x16
FC12-180CQ	12	180/10HR	522	240	219	244	55.3	L17	C	M8x30
FC12-180CT	12	180/10HR	522	240	219	224	55.3	T5	C	M8x16
FC12-200AQ	12	200/10HR	522	240	219	244	58.2	L17	C	M8x30
FC12-200AT	12	200/10HR	522	240	219	224	58.2	T5	C	M8x16
FC12-220AQ	12	220/20HR	522	240	219	244	60.5	L17	C	M8x30
FC12-220AT	12	220/20HR	522	240	219	244	60.5	L17	C	M8x30
FC12-220AT	12	220/20HR	522	240	219	224	60.5	T5	C	M8x16
FC12-220BT	12	220/10HR	520	269	203	209	68	T5	C	M8x16
FC12-250AQ	12	250/10HR	520	268	220	245	70	L17	C	M8x30
FC12-250AT	12	250/10HR	520	268	220	225	70	T5	C	M8x16